

Contactors, 3 pole, 380 V 400 V: 15 kW, 24 V DC, DC operation, Screw terminals



Part no. DILMT32(RDC24)

190982

EL Number

4100415

(Norway)

Product name	Eaton Moeller® series DILMT Contactor
Part no.	DILMT32(RDC24)
EAN	4015081912056
Product Length/Depth	97.5 millimetre
Product height	82 millimetre
Product width	36 millimetre
Product weight	0.36 kilogram
Certifications	IEC/EN 60947 GB14048 EN 60335-1
Product Tradename	DILMT
Product Type	Contactors
Product Sub Type	None
Globally Marketable	No
Countries	Germany Portugal Belgium United Kingdom of Great Britain and Northern Ireland Denmark Poland Saudi Arabia Czech Republic Morocco Hungary Romania Sweden Slovakia Turkey China France Austria Finland Italy Norway United Arab Emirates Spain Netherlands Switzerland Latvia Israel
Fitted with:	Varistor suppressor circuit
Number Of Poles	Three-pole
Application	Contactors for Motors
Connection to SmartWire-DT	No
Degree of protection	IP20
Frame size	FS2
Lifespan, electrical	1,000,000 Operations (at 400V, AC-3)
Lifespan, mechanical	10,000,000 Operations (DC operated)
Operating frequency	3600 mechanical Operations/h (DC operated)
Overvoltage category	III
Pollution degree	3
Product category	Contactors
Rated impulse withstand voltage (Uimp)	6000 V AC
Used with	DILT-XHI01(10)
Utilization category	AC-1: Non-inductive or slightly inductive loads, resistance furnaces AC-3: Normal AC induction motors: starting, switch off during running

		AC-4: Normal AC induction motors: starting, plugging, reversing, inching
Voltage type		DC
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		55 °C
Ambient storage temperature - min		40 °C
Ambient storage temperature - max		80 °C
Climatic proofing		Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Terminal capacity (solid)		2 x (0.75 - 2.5) mm ² 1 x (0.75 - 2.5) mm ² 1 x (1 - 10) mm ² , Main cables
Terminal capacity (stranded)		1 x (1 - 10) mm ² 2 x (1 - 10) mm ²
Stripping length (main cable)		14 mm
Screw size		M5, Terminal screw M3.5, Terminal screw
Screwdriver size		2, Terminal screw, Pozidriv screwdriver 2, Terminal screw, Control circuit cables, Pozidriv screwdriver
Tightening torque		0.8 Nm, Screw terminals 2 Nm, Threaded ring
Rated breaking capacity at 380/400 V		256 A
Rated insulation voltage (Ui)		690 V
Rated operational current (Ie) at AC-1, 380 V, 400 V, 415 V		40 A
Rated operational current (Ie) at AC-3, 220 V, 230 V, 240 V		32 A
Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V		32 A
Rated operational power at AC-3, 380/400 V, 50 Hz		15 kW
Rated operational voltage (Ue) at AC - max		660 V
Rated control supply voltage (Us) at AC, 50 Hz - min		0 V
Rated control supply voltage (Us) at AC, 50 Hz - max		0 V
Rated control supply voltage (Us) at AC, 60 Hz - min		0 V
Rated control supply voltage (Us) at AC, 60 Hz - max		0 V
Rated control supply voltage (Us) at DC - min		24 V
Rated control supply voltage (Us) at DC - max		24 V
Number of auxiliary contacts (normally closed contacts)		0
Number of auxiliary contacts (normally open contacts)		0

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC000066)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Power contactor, AC switching (ecl@ss10.0.1-27-37-10-03 [AAB718015])		
Rated control supply voltage Us at AC 50HZ	V	0 - 0
Rated control supply voltage Us at AC 60HZ	V	0 - 0
Rated control supply voltage Us at DC	V	24 - 24
Voltage type for actuating		DC
Rated operation current Ie at AC-1, 400 V	A	40
Rated operation current Ie at AC-3, 400 V	A	32
Rated operation power at AC-3, 400 V	kW	15
Rated operation current Ie at AC-4, 400 V	A	0
Rated operation power at AC-4, 400 V	kW	0
Rated operation power NEMA	kW	0
Modular version		No
Number of auxiliary contacts as normally open contact		0
Number of auxiliary contacts as normally closed contact		0
Type of electrical connection of main circuit		Screw connection

Number of normally closed contacts as main contact		0
Number of normally open contacts as main contact		3